U.S. Patent Application Serial No. 10/030,099 Response dated November 7, 2003 Reply to OA of August 7, 2003

IN THE CLAIMS

Please amend claims 1, 6-8 and 11 as follows:

- 1. (Currently Amended): A printed matter having a receiving layer for an ink jet recording ink for printing variable information formed on the entire or a part of the surface of a printing paper, said printing paper having an ink layer containing fixed information printed by using a printing method selected from lithographic printing, relief printing and intaglio printing.
- 2. (Original): The printed matter according to Claim 1, wherein the receiving layer for an ink jet recording ink comprises at least two layers containing different ingredients respectively, at least one layer of them being a receiving layer comprising an ink-absorbing resin as its main ingredient and at least the other layer of them being a receiving layer comprising an ink-fixing resin as its main ingredient.
- 3. (Original): The printed matter according to Claim 2, wherein the receiving layer comprising an ink-absorbing resin as its main ingredient is a receiving layer for an ink jet recording ink containing at least one ink-absorbing resin selected from the group consisting of proteins, starches, celluloses, polyvinyl alcohols, polyvinyl acetals and polyvinylpyrrolidones.

U.S. Patent Application Serial No. 10/030,099

Response dated November 7, 2003

Reply to OA of August 7, 2003

4. (Previously Presented): The printed matter according to Claim 2, wherein the receiving

layer comprising an ink-absorbing resin as its main ingredient is a receiving layer for an ink jet

recording ink further containing a filler.

5. (Previously Presented): The printed matter according to Claim 2, wherein the receiving

layer comprising an ink-fixing resin as its main ingredient is a receiving layer for an ink jet recording

ink containing at least one ink-fixing resin selected from the group consisting of resins having a

cationic group in their molecules.

6. (Currently Amended): The printed matter according to Claim 1, wherein the receiving

layer is formed at least on the print film of the ink layer used for printing containing the fixed

information.

7. (Currently Amended): The printed matter according to Claim 6, wherein the fixed

information is printed with an oil-based ink by using the lithographic printing method or the relief

printing method, and the receiving layer for an ink jet recording ink is formed at least on the print

film ink layer of the oil-based ink, the receiving layer comprising one layer or two or more layers

containing different ingredients, wherein the layer adjoining the print film of the oil-based ink

contains a film-forming acrylic resin obtained by emulsion polymerizing monomers containing 15%

-3-

U.S. Patent Application Serial No. 10/030,099 Response dated November 7, 2003 Reply to OA of August 7, 2003

by weight or more of a (meth)acrylic ester compound containing an alkyl group having 8 to 18 carbon atoms.

8. (Currently Amended): The printed matter according to Claim 6, wherein the fixed information is printed with an oil-based ink by using the lithographic printing method or the relief printing method, and the receiving layer for an ink jet recording ink is formed at least on the print film ink layer of the oil-based ink, the receiving layer comprising one layer or two or more layers containing different ingredients, wherein the layer adjoining the print film ink layer of the oil-based ink is formed from a coating agent further containing 1 to 8% by weight of at least one film forming-improving agent selected from the group consisting of the compounds represented by the following general formulas (1) to (3):

$$Y^{1}-O-(X^{1}-O)n-Z^{1}$$
 (1)

$$Y^2$$
-O- X^2 -O- Z^2 (2)

$$Y^{3}$$
-OCO- X^{3} -COO- Z^{3} (3)

wherein X^1 denotes an alkylene group having 2 to 4 carbon atoms, Y^1 and Z^1 each denote an alkylene group having 1 to 4 carbon atoms, n denotes an integer of 1 to 4; X^2 denotes an alkylene group having 2 to 8 carbon 10 carbon atoms, Y^2 denotes H or an alkyl group having 1 to 11 carbon atoms, Z^2 denotes an alkyl group having 4 to 11 carbon atoms or an acyl group having 4 to 11 carbon atoms with the proviso that Y^2 is H, Z^2 denotes an acyl group having 4 to 11 carbon atoms with the proviso that Z^2 denotes an acyl group having 2 to 11 carbon

U.S. Patent Application Serial No. 10/030,099

Response dated November 7, 2003

Reply to OA of August 7, 2003

atoms with the proviso that Y² is an alkyl group having 4 to 11 carbon atoms; X³ denotes a residual

group of an aliphatic dibasic acid or an aromatic dibasic acid; and Y³ and Z³ each denotes an alkyl

group having 1 to 11 carbon atoms.

9. (Previously Presented): A printed matter, characterized in that variable information is

printed by an ink jet recording method on the receiving layer recited in Claim 1.

10. (Previously Presented): A method for producing the printed matter according to Claim

2, characterized by printing fixed information and then forming the receiving layer for an ink jet

recording ink with a coater or a printer by an in-line system.

11. (Currently Amended): A method for producing the printed matter according to Claim

7, characterized by forming the receiving layer for an ink jet recording ink with a coater or a printer

by an in-line system on a printed surface printed surface still in a wet condition immediately after

printing the fixed information with an oil-based ink.

12. (Previously Presented): The method for producing a printed matter according to Claim

10, wherein the receiving layer for an ink jet recording ink is formed with a coater equipped with an

anilox roll and a rubber roll.

-5-